

# Model PR-950



## Featuring:

- Serial line thermal printer with stationary print head
- Prints up to <sup>1</sup>52 characters/line in normal or bold type fonts.
- Plugs in directly to JMC display-type NAVTEX receivers.
- Serves as external printer for <sup>2</sup>NT-900 printing-type NAVTEX receiver.
- Compatible with PR-900 dot matrix printer
- Outputs readiness status signals for use in AIS and other printing applications.
- Housed in rust-free rugged ABS plastic cabinet

## Specifications

- **Print Head Type:** Line thermal head
- **Max. No. of Printable Characters:** <sup>1</sup>52 characters/line
- **Character Font Size:** 12×8 dots, 2.1 mm(H) X 1.8 mm(W)
- **Recording Paper:** Thermo-sensitive, 112 mm×25 m/roll
- **Hardware Interface:** 8-pin connector and DSUB-9 (RS-232C)
- **Baud Rate:** 110 and 4800, selectable
- **Flow Control:** None (110 baud), status signal in hex (4800 baud)
- **Power Requirements:** 11-40 VDC (nominal) 12 W (printing)
- **Dimensions:** 167(H)X182(W)X84(D) mm, less mounting tabs
- **Weight:** Approx. 1.5 kg (with standard paper roll)

<sup>1</sup>: Up to 40 characters/line when interfaced with NT-1800 and NT-2000.

<sup>2</sup>: Optional modification kit is required for NT-900.