

Model V-6802P



Featuring:

- GPS track plotter and dual frequency fish finder housed in compact cabinet
- 6.4-inch daylight-viewing TFT LCD with screen sleep mode
- Full screen display of plotter, fish finder, CDI or satellite information pages
- Split screen display of simultaneous track-plotting/fish-finding operation
- Split display of high and low frequency echograms or full display of either frequency
- A-scope display for instant fish size assessment in deep range operations
- Built-in electronic chart of user-specified area requires no chart cartridges.

Specifications

- **Screen:** 6.4" backlit QVGA TFT LCD, daylight-viewing
- **GPS Receiver:** 18 channels, 1575.42 MHz C/A code, WAAS/DGPS-ready
- **Map Coverage:** User-specified area between 85° N/S, north-up Mercator
- **Map Scale:** 1/2250 to 1/25 million or 0.1 to 1500 n.m.
- **Waypoints:** 1800/4000 with/without name tags, plus 1 MOB waypoint
- **Track Storage:** 8000 points
- **Transducer Frequencies:** 50 kHz and 200 kHz (single crystal)
- **Transmit Power (RMS):** 400W
- **Ranges:** 2.5 to 1000 m/fthm/br in 15 steps
- **Power Requirements:** 11-40 VDC, 22W
- **Weight:** 2.01 kg with mounting bracket
- **Size:** 238/196W × 217/196H × 194D mm with/without bracket