

# Model NP-30MR



Photo shows C-MAP chart with Unicode version software installed.



C-MAP is a trademark of Jeppesen Italia S. r. l.

## Featuring:

- 10.4-inch VGA daylight-viewing TFT LCD screen
- Built-in 18-channel WAAS/DGPS-ready GPS receiver.
- Built-in worldwide background map for general navigation purposes
- Supports C-MAP **MAX** charts as well as existing C-MAP **NT/NT+** charts.
- Displays coordinates in LAT/LON, UTM or Loran-C TD's.
- Devoted MOB key for storage of current position
- Advanced grounding alarm to warn against obstructions, rocks, shoals, etc.
- Interfaces with specified radar scanner to constitute full feature color radar.
- Interfaces with **RT-2500** to display other vessels' position across plotter screen.
- Interfaces with **BV-6100** to constitute full function dual frequency color fish finder.
- Interfaces with AIS receiver to overlay AIS data on charts.
- Interfaces with up to 2 NTSC/PAL video cameras.
- Optional C-COM module for receiving **C-WEATHER** service

## Specifications

- **Screen:** 10.4" VGA TFT LCD, daylight-viewing
- **GPS Receiver:** 18-channel parallel, 1575.42 MHz C/A code, WAAS/DGPS-ready
- **Map Coverage:** Worldwide background map + optional C-MAP **MAX NT/NT+** cards
- **Map Coordinates Systems:** LAT/LON, UTM and Loran-C TD's
- **Track Storage:** 5,000 points × 5 tracklines (25,000 in total)
- **Waypoints:** 2,000
- **Routes:** 20 with up to 100 waypoints
- **Card Slots:** 2
- **Power Requirements:** 11-40 VDC, 21W
- **Weight:** 4.8 kg with mounting bracket
- **Size:** 410/366W × 398/275H × 98D mm with/without bracket